

In re Application of: Poplawski *et al.*
Application No.: 10/637,161
Atty Docket No.: 36400.35US2

Examiner: T. Lewis
Art Unit: 3681

IN THE SPECIFICATION:

On Page 16, please replace the second full paragraph (which continues to Page 17) with the following:

To provide for the easy mounting of the IHT 10 to a vehicle frame 78, as illustrated in Figs. 18 and 19, the IHT 10 includes a front mounting bracket 80 and a top mounting bracket 82. Generally, the front mounting bracket 80 is u-shaped having a first side that includes openings for receiving bolts that attach the front mounting bracket 80 to the IHT housing, a second side, parallel to the first side, having at least one opening for receiving a bolt that attaches the front mounting bracket 80 to a side of the vehicle frame 78, and a third side, lying in a horizontal plane, the joins the first side to the second side. Likewise, the top mounting bracket 82 is u-shaped having a first side that includes openings for receiving bolts that attaches the top mounting bracket 82 to the IHT housing, a second side, parallel to the first side, having at least one opening for receiving a bolt that attaches the top mounting bracket 82 to a side of the vehicle frame 78, and a third side, lying in a vertical plane, ~~the~~ that joins the first side to the second side. It is preferable that the fasteners used to attach the mounting brackets to the housings be the same fasteners used to attach the first side housing 26 to second side housing 28.